	Belt	Top Cover Thickness (mm)	Top Cover Construction	Bottom Cover Construction	Overall Thickness (mm)	Colour	Min. Pulley Dia. Drive (mm)	Min. Pulley Dia. Backflexing (mm)	Coefficient of Friction (Steel)	Weight (kg/m2)	Fabric Construction	Tension (1% elongation)	Anti-static	Temp. Resistance (product temp ℃)	FDA/USDA Approved	Stock Width (mm)
PU BELTS	**C07UU**	N/A	Impregnated	PU Impregnated	0.5mm	Green	knife edge	10mm	0.3	0.35	flexible	6N/mm	✓	-10 to 100℃	✓	1500
	1RA41PU	0.4mm	smooth matt	textile Impregnated	0.9mm	White	knife edge	10mm	0.2	1	flexible	4N/MM		-20 to 100℃	✓	2000
	1R2M1SPU/PO	0.2mm	smooth matt	fabric Impregnated	0.7mm	Blue	knife edge	10mm	0.2	0.8	flexible	6N/mm	✓	-20 to 100℃	✓	2000
	1PURB65/FW	0.65mm	satin matt	fabric Impregnated	1.3mm	White	knife edge	20mm	0.2	1.45	flexible	7N/mm		-40 to 95℃	✓	2000
	2RHA15-2PU	1.5mm	smooth matt	fabric skim coated	3.7mm	Transparent	100mm	150mm	0.3	4.2	rigid	10N/mm	✓	-20 to 100℃	✓	2000
	2RA4PUB	0.4mm	smooth matt	textile Impregnated	1.7mm	Black	15mm	30mm	0.2	1.8	rigid	17N/mm	✓	-20 to 100℃		3100
	2RA41PU	0.75mm	smooth matt	textile Impregnated	2.35mm	Transparent	50mm	100mm	0.2	2.7	rigid	13N/mm	✓	-20 to 100℃	✓	2000
	2R5U0U2MT	0.2mm	smooth matt	PU Impregnated	1.4mm	White	knife edge	25mm	0.2	1.5	rigid	6N/mm		-20 to 100℃	✓	2000
	2R5U0U2HF	0.2mm	smooth shiny	PU Impregnated	1.4mm	White	knife edge	25mm	0.2	1.5	rigid	6N/mm		-20 to 100℃	✓	2000
	2R/LR2M1SPUB	0.2mm	smooth matt	fabric impregnated	1.4mm	Blue	knife edge	25mm	0.2	1.5	rigid	10N/mm		-40 to 100℃	✓	2000
	2EPAS2M-1SPU	0.2mm	smooth matt	fabric	1.3mm	Blue	10mm	40mm	0.18	1.44	flexible	8.5N/mm		-40 to 110℃	✓	2000
	1RA-LW	N/A	nipple finish	PU bare	2mm	Blue	knife edge	15mm	0.2	0.9	flexible	N/A		-40 to 110℃	✓	100mm wide
	2PURX30/EW	0.2mm	smooth matt	fabric impregnated	1.4mm	Blue	knife edge	25mm	0.2	1.5	rigid	10N/mm		-40 to 100℃	✓	2000
PVC FOOD GRADE	**2LR51N**	0.5mm	flat	fabric impregnated	1.9mm	White	30mm	60mm	0.2	2	rigid	10N/mm		-10 to 110℃	✓	2000
	2LR51NB	0.5mm	flat	fabric impregnated	1.9mm	Blue	30mm	60mm	0.2	2	rigid	10N/mm		-10 to 110℃	✓	2000
	2R71N	0.7mm	flat	fabric impregnated	2.4mm	White	40mm	60mm	0.2	2.7	rigid	10N/mm		-10 to 110℃	✓	2000
	2R201N	2mm	flat	fabric impregnated	3.7mm	White	60mm	120mm	0.2	4.2	rigid	10N/mm		-10 to 110℃	✓	2000
	3R101NAD	1mm	flat	fabric impregnated	4.5mm	White	100mm	200mm	0.2	5.3	rigid	13N/mm		-10 to 110℃	✓	2000
	2LR8N1N	0.5mm	1mm nipple	fabric impregnated	2.6mm	White	30mm	60mm	0.2	2.2	rigid	10N/mm		-10 to 100℃	✓	2000
	2RST201NS	3.6mm	saw tooth	fabric impregnated	4.8mm	White	60mm	120mm	0.2	4.2	rigid	10N/mm		-20 to 100℃	✓	2000
	2E78RN	0.7mm	flat	PVC inverted diamond	3.2mm	White	50mm	80mm	0.35	3.3	flexible	15N/mm		-10 to 110℃	✓	2000
	2E78RNB	0.7mm	flat	PVC inverted diamond	3.2mm	Blue	50mm	80mm	0.35	3.3	flexible	15N/mm		-10 to 110℃	✓	2000
	2E208RN	2mm	flat	PVC inverted diamond	4.5mm	White	80mm	140mm	0.35	5.2	flexible	15N/mm		-10 to 110°C	✓	2000
	2E7SN8RNB	0.7mm	sharp nipple	PVC inverted diamond	4mm	Blue	50mm	80mm	0.35	3.3	flexible	15N/mm		-10 to 110℃	✓	1500
BAKERY BELTS	**1RV00N**	N/A	Polyester felt	textile impregnated	3.2mm	White	20mm	30mm	0.18	1.8	rigid	4N/mm		-15 to 110℃	✓	2000
	NVN25	N/A	Both sides compressed polyester		2.5mm	White	10mm	20mm	0.18	1.8	rigid	13N/mm	✓	+10 to 120℃	✓	2000
	2R00N	N/A	Both sides PU impregnated		1.6mm	White	20mm	20mm	0.18	1.7	rigid	4N/mm		-10 to 110℃	✓	2000
	2EC/LRA01SPU	N/A	Cotton/polyester	PU/polyester	1.3mm	White	knife edge	15mm	0.2	1.1	rigid	6N/mm	✓	-40 to 110℃	✓	2000
	2REZ00N	N/A	rayon/polyester	PU impregnated	1.9mm	White	knife edge	40mm	0.2	1.4	rigid	5N/mm		-40 to 110℃	✓	2000
	2LR8R1N	0.5mm	inverted diamond	fabric impregnated	2.2mm	White	30mm	60mm	0.2	2.2	rigid	10N/mm		-10 to 100℃	✓	2000
	CNB6EB	N/A	smooth matt	impregnated polyester	1.05mm	White	knife edge	20mm	0.15	1.1	flexible	4N/mm	✓	-40 to 80℃	✓	2400
	2RSA10MG-0SPU	0.7mm	minigrip	fabric	2.75mm	White	60mm	80mm	0.18	2.1	rigid	6N/mm	✓	-40 to 100℃	✓	2000
	2RU0U0PU	N/A	Both sides fabric impregnated		1.1mm	White	12mm	30mm	0.2	1.05	rigid	10N/mm	✓	-40 to 95℃	✓	2000

SILICONE	1BRA21SIR	0.2mm	silicone rubber	fabric	0.7mm	White	knife edge	12mm	0.2	0.65	rigid	6N/mm	✓	-40 to 180℃	✓	2000
	2LRA50SIR	0.5mm	silicone rubber	fabric	1.8mm	White	60mm	60mm	0.18	1.8	rigid	8N/mm	✓	-40 to 150℃	✓	2000
	2BRA21SIR/N	0.2mm	silicone rubber	fabric	1.5mm	White	50mm	50mm	0.2	1.7	rigid	10N/mm	✓	-30 to 120℃	✓	2000
PVC GENERAL	1RASX9W0F	0.9mm	fabric impression	low noise fabric	1.4mm	Black	knife edge	20mm	0.18	1.3	rigid	11N/mm	✓	-10 to 90℃		2000
	2AQ8i0-0F	0.8mm	inverted oval	low noise fabric	2.1mm	Black	20mm	50mm	0.2	1.8	rigid	10N/mm	✓	-15 to 90℃		2000
	2RVA4M0F	0.4mm	smooth matt	fabric	2mm	Black	25mm	50mm	0.18	2.2	rigid	8N/mm	✓	-10 to 90℃		3250
	2RVA50FAD	0.5mm	smooth shiny	fabric	2.1mm	Petrol	25mm	50mm	0.18	2.3	rigid	8N/mm	✓	-10 to 90℃		3250
	2LRAZ11N	N/A	Both sides PU impregnated		1.4mm	Black	30mm	30mm	0.2	1.5	rigid	8N/mm	✓	-15 to 110℃		2000
	3LRARX10F	N/A	fabric impregnated	low noise fabric	2.6mm	Black	60mm	80mm	0.18	2.8	rigid	12N/mm	✓	-15 to 110℃		2000
	NVN400	N/A	Both sides compressed polyester		4mm	Grey	65mm	65mm	0.18	2.5	rigid	14N/mm	✓	10 to 120℃		2000
	NVN60HC	N/A	Both sides compressed polyester		6mm	Grey	100mm	100mm	0.18	3.4	rigid	16N/mm		10 to 120℃		
	2E78RF	0.7mm	flat	PVC inverted diamond	3.2mm	Black	50mm	80mm	0.35	3.3	flexible	15N/mm	✓	-15 to 90℃		2000
	2RRX10M0FV	1mm	smooth matt	low noise fabric	2.4mm	Black	50mm	80mm	0.18	2.7	rigid	11N/mm	✓	-10 to 90℃		2000
	2EK/R20-1NH85	2mm	flat	PU skim coated	4.5mm	Petrol	120mm	180mm	0.2	5.8	rigid	22N/mm	✓	-10 to 110℃		3300
	3EK/R20-1NH85	2mm	flat	PU skim coated	5.5mm	Petrol	120mm	180mm	0.2	7	rigid	28N/mm	✓	-10 to 110℃		3300
	2E7M0FV	0.7mm	flat	fabric	2.4mm	Black	40mm	70mm	0.18	2.7	flexible	15N/mm	✓	-15 to 90℃		3200
	3EK20LG-2F	2mm	snakeskin	fabric impregnated	7mm	Petrol	300mm	400mm	0.2	7.8	rigid	50N/mm	✓	-15 to 90℃		2000
PVC PROFILE	2LRARX12LR0FSV	1.2mm	longitudinal	low noise fabric	3mm	Black	50mm	80mm	0.18	4	rigid	11N/mm	✓	-25 to 90℃		2000
	2RRX20LR0FS	2mm	longitudinal	low noise fabric	3.8mm	Grey	60mm	110mm	0.18	4.2	rigid	11N/mm	✓	-25 to 90℃		2000
	2RRASG0FS	3.6mm	roughtop	fabric	5.9mm	Green	60mm	120mm	0.2	4	rigid	10N/mm	✓	-25 to 70℃		2000
	2RRXSG0FSV	3.6mm	roughtop	low noise fabric	5.7mm	Black	60mm	120mm	0.18	4	rigid	11N/mm	✓	-25 to 70℃		2000
	2RRX10BW0FSV	1mm	basket weave	low noise fabric	2.7mm	Black	50mm	80mm	0.18	2.7	rigid	11N/mm	✓	-25 to 70℃		2000
	2RRX10LG0FS	1mm	snakeskin	low noise fabric	2.1mm	Grey	30mm	60mm	0.18	2	rigid	10N/mm	✓	-25 to 70℃		2000
	GUTW12A	N/A	low grip	fabric	2mm	Green	50mm	50mm	0.25	1.2	rigid	4N/mm	✓	-20 to 70℃		1000
RUBBER R/TOP	2RT150	4mm	roughtop	fabric	6.4mm	Black	50mm	80mm	0.35	5.37	rigid	20N/mm		-20 to 120℃		1800
	3RTB150N	5.2mm	roughtop	fabric	7.2mm	Brown	75mm	110mm	0.4	5.86	rigid	26N/mm		-15 to 120℃		1800
	3TPUSG	5mm	roughtop	skim coated	6.8mm	Orange	50mm	50mm	0.4	5.5	rigid	24N/mm		-15 to 120℃		1800
	EP150M	6mm	cockscomb	fabric	6.4mm	Blue	50mm	80mm	0.35	5	rigid	14N/mm		-10 to 120℃		1800
	3RT200M	5mm	roughtop	fabric	8.3mm	Black	85mm	140mm	0.35	6.2	rigid	26N/mm		-20 to 120℃		1800
	3 BIG RED	5mm	roughtop	fabric	6.8mm	Red	50mm	50mm	0.4	5.5	rigid	24N/mm		-20 to 120℃		1800
	WEDGEGRIP	5mm	wedgegrip	fabric	8mm	Tan	120mm	120mm	0.3	5.1	rigid	11N/mm		-29 to 65℃		1800
SOLID WOVEN	2BSW120	0.9mm	flat	brushed fabric	3.4mm	Black	51mm	51mm	0.25	3.9	flexible	11N/mm	✓	-29 to 82℃		1800
	CT120B	2.2mm	crescent top	brushed fabric	5.6mm	Black	51mm	51mm	0.35	4.6	flexible	11N/mm	✓	-40 to 82℃		1800
	CT200	2.5mm	crescent top	brushed fabric	6.8mm	Black	75mm	75mm	0.25	6	flexible	17N/mm	✓	-29 to 82℃		1800
	COS250	0.9mm	flat	brushed fabric	5.8mm	Black	150mm	150mm	0.25	6.3	flexible	22N/mm	✓	-29 to 82℃		1800
	CBS200	0.9mm	both sides PVC cover		6.8mm	Black	125mm	125mm	0.5	6.3	flexible	17N/mm	✓	-29 to 82℃		1800
	CTW120	2.2mm	crescent top	brushed fabric	5.6mm	White	51mm	51mm	0.35	4.6	flexible	11N/mm	✓	-40 to 82℃	✓	1800